

```

=====
c
c
c   gpwave: Generates time-series of profiles of
c   left-moving "wave" ( $f(t+x) = \text{constant}$ ) and outputs to
c   stdio in form suitable for subsequent plotting with
c   'gnuplot'.
c
c   For parametric surface plots 'gnuplot', expects three
c   numbers per line:
c
c       x(i), y(j), f(i,j)
c
c   with all data points with the same x(i) on contiguous
c   lines (a group) and with empty lines separating
c   groups. A quick glance at some sample output from this
c   program should make the arrangement clear.
c
=====

```

```

program      gpwave

implicit    none

integer      i4arg

integer      maxn
parameter ( maxn = 100 )

real*8      f
real*8      x(maxn)
integer      i,          j,          n,          nx,
&           nt
real*8      h,          t,          dt

```

```

n = i4arg(1,-1)
if( n .lt. 1 .or. n .gt. maxn ) goto 900
nx = n
nt = n

h = 1.0d0 / (nx - 1)
x(1) = 0.0d0
do j = 1 , nx - 1
    x(j+1) = x(j) + h
end do

t = 0.0d0
dt = 1.0d0 / (nt - 1)
do i = 1 , nt
    do j = 1 , nx
c-----
c          Output the cordinates and function value, three
c          per line, first coordinate (time) constant.
c-----
        write(*,*) t, x(j), f(mod((x(j) + t),1.0d0))
    end do
c-----
c          Empty line separates groups with distinct
c          first coordinate.
c-----

        write(*,*)
        t = t + dt
    end do
stop

900 continue
    write(0,*) 'usage: gpwave <n>'
stop
end

```

```
c-----  
c   Gaussian function.  
c-----  
double precision function f(x)  
  implicit      none  
  real*8        x  
  f = exp(-((x-0.5d0)/0.1d0)**2)  
  return  
end
```

```

#####
# Building and running 'gpwave' on sgi1.
#####
sgi% pwd
/usr/people/phys410/fd/wave

sgi% ls
Makefile  gpin      gpwave.f

sgi% make
f77 -g -64 -c gpwave.f
f77 -g -64 -L/usr/local/lib gpwave.o -lp410f -o gpwave

#####
# 'gpwave' expects a single argument, 'n'.  It then
# generates data which can be plotted as a two-dimensional
# surface (z(x,y)) using 'gnuplot'.
#####
sgi% gpwave
usage: gpwave <n>

#####
# Generate data on a 51 x 51 mesh and save to file 'output'.
#####
sgi% gpwave 51 > output

sgi% more gpin
#####
# Sample gnuplot commands to read data in file 'output'
# and plot as 'parametric' surface plot with hidden lines
# removed.
#####
set terminal postscript landscape
set output "output.ps"

```

```
set parametric
set hidden
splot "output" with lines
quit
```

```
#####
# Make the plot.
#####
sgi% gnuplot < gpin
```

```
sgi% ls
Makefile      gpwave*      gpwave.o     output.ps
gpin          gpwave.f     output
```

```
#####  
# Sample gnuplot commands to read data in file 'output'  
# and plot as 'parametric' surface plot with hidden lines  
# removed.  
#####  
set terminal postscript landscape  
set output "output.ps"  
set parametric  
set hidden  
splot "output" with lines  
quit
```

"output" —

